



194.00 EUR  
incl. 19% VAT, plus [shipping](#)

**Support:**  [Specifications \[EN\]](#)

- INTEL® 945GSE + ICH7M Chipset
- Support INTEL® Atom N270 CPU(45nm,512K Cache, 1.60 GHz, 533 MHz FSB)
- Build-in INTEL®GMA 950 Graphics Core
- Integrated LVDS support 18-bit TFT LCD
- Supports Dual Gigabit LAN
- Integrated ALC662 HD Audio CODEC with 6-CH
- Support Watch dog Technology
- Mini-ITX Form Factor(148mm x 102mm)

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>1. CPU</li> <li>1. Chipset</li> <li>1. Memory</li> <li>1. Storage</li> <li>1. Audio</li> <li>1. Ethernet LAN</li> <li>1. LVDS</li> <li>1. USB</li> <li>1. Special Features</li> <li>1. Rear Panel I / O</li> </ul> | <ul style="list-style-type: none"> <li>1. INTEL ® Atom N270 CPU(45nm,512K Cache, 1.60 GHz, 533 MHz FSB)</li> <li>1. INTEL® 945GSE + ICH7M chipset</li> <li>2. Build-in INTEL® GMA 950 Graphics Core(Share Memory Size: 128/224MB)</li> <li>3. Front Side Bus 533MHz</li> <li>1. 1 * SO-DIMM Sockets for un-buffered Single Channel DDR2 533/400 SDRAM up to 2 GB</li> <li>1. 1 * Serial ATA2 3Gb/s connectors</li> <li>2. 1 * Ultra DMA 133/100 IDE connector</li> <li>1. Realtek ALC662 6-Channel HD Audio Codec</li> <li>1. 2 * Realtek RTL8111DL PCI-E Gigabit Ethernet LAN</li> <li>1. Onboard 18-bit dual channel LVDS connector</li> <li>1. Embedded 4 * USB 2.0</li> <li>2.</li> <li>1. Intel Diamond Ville Platform</li> <li>2. Support ACPI S3</li> <li>3. Support CPU Smart FAN</li> <li>1. 2 * USB 2.0 ports</li> <li>2. 1 * PS KB connector</li> <li>3. 2 * RJ-45 port</li> <li>4. 3 * Audio I/O ports ( Line-in, MIC and line-out )</li> <li>5. 1 * 12V DC jack</li> <li>6. 1 * DVI-I port</li> </ul> |
|---|--|

1. Internal I / O

1. 1\* USB 2.0 headers for 2 USB 2.0 ports
2. NB / Chassis Fan connectors;
3. 1 \* 20-pin ATX Power connector
4. 1 \* 32-pin LVDS header & 1 \* GPIO header & 1 \* Parallel header
5. 2 \* RS232 COM headers & 1 \* RS422/485 header
6. 1 \* Audio header & 1 \* CF CARD header
7. 1 \* Mini PCI-E connector

1. BIOS

1. Award 8MB DIP Flash ROM

1. Form Factor

1. Mini ITX Form Factor(148mm x 102mm)

1. Functional

1. ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation

1. Certificate

1. CE, FCC, RoHS

1. Temperature

1. Operating within 0~60 centigrade
2. Storage within -20-85 centigrade

**Product Accessories**

- DVI-I to CRT Converter
- Manual
- CD
- 1x SATA cable
- SATA power cable