


198.00 EUR  
incl. 19% VAT, plus [shipping](#)



**Support:**  [Specifications \[EN\]](#)

- Intel® HM67 Express Chipset
- Supports Intel Core™ i3, i5, i7 Mobile Processors
- 2 \* SO-DIMM Dual Channel DDR3-1333/1066 up to 16GB
- Intel 82577LM Gigabit LAN
- PCI Express x16 2.0 Slot, PCI Express Mini Card Slot
- Integrated 24-bit Dual Channel LVDS
- 2-ports SATA 6Gb/s & 3-ports SATA 3Gb/s with RAID 0, 1, 5, 10 & JBOD Support
- HDMI, DVI-D, and VGA Video Outputs
- Built-in Watchdog Timer Technology
- Mini-ITX Form Factor (170mm x 170mm)
- Includes CPU Heatsink/Fan for <35W Processors

#### **CPU**

Intel Core i3, i5, i7 mobile processors  
Socket G2 (rPGA988B), Includes CPU Heatsink / fan for <35W processors

#### **Chipset / Video**

Intel HM67 Express Chipset  
Intel HD Graphics ( requires compatible CPU with built-in GPU )

#### **Memory**

2 \* SODIMMs Sockets for un-buffered dual channel  
DDR3-1333/1066 up to 16 GB

---

<b>Expansion Slots</b>	1 * PCI Express x16 2.0 (by 16-lane) slot 1 * PCI Express Mini Card slot
<b>Storage</b>	2 * Serial ATA III 6Gb/s & 3 * Serial ATA II 3Gb/s connectors Support RAID 0,1,5,10
<b>Audio</b>	VIA VT 1705 6-Channel HD Audio
<b>Ethernet LAN</b>	Intel 82577LM Gigabit Ethernet LAN
<b>LVDS</b>	Onboard 24-bit dual channel LVDS connector
<b>USB</b>	Embedded 2 * USB 3.0 & 8 * USB 2.0/1.1
<b>Special Features</b>	Supports ACPI S3, CPU Smart FAN, All solid capacitors Watchdog hardware monitor
<b>Rear Panel I / O</b>	2 * USB 3.0 & 4 * USB 2.0/1.1 ports 1 * PS/2 KB/mouse combo connector 1 * RJ-45 port 1 * HDMI port & 1 * VGA port & 1 * DVI-D port 1 * Audio port (Line-in, MIC and Line-out) 1 * Coaxial Out & 1 * Optical Out
<b>Internal I / O</b>	2 * USB 2.0/1.1 headers for 4 USB ports 1 * 24-bit dual channel LVDS header 1 * Serial header ( RS232/422/485 ) 1 * GPIO header 1 * Audio header, 1 * Front panel header 1 * 24-pin ATX power connector, 1 * 4-pin 12V ATX power connector
<b>BIOS</b>	AMI EFI 32MB SMT Flash ROM
<b>Certificate</b>	CE, FCC, RoHS, EuP
<b>Functional</b>	ATM, Automation, medical Equipment, Security, Digital Signage, POS, General Application, Gaming Machine, Transportation
<b>Temperature</b>	Operating within 0~60 centigrade Storage within -20-85 centigrade
<b>Form Factor</b>	Mini-ITX Form Factor (170mm x 170mm)
<b>Product Accessories</b>	
- COM cable	
- Manual	
- CD	
- 1x SATA cable	
- I/O shield	
- CPU fan	
- Thermal grease	