



149.00 EUR
incl. 19% VAT, plus [shipping](#)



Support:  [Specifications \[EN\]](#)

- INTEL® 945GSE + ICH7M Chipset
- Support INTEL® Atom N270 CPU(45nm,512K Cache, 1.60 GHz, 533 MHz FSB)
- Build-in INTEL®GMA 950 Graphics Core
- Integrated LVDS support 18-bit TFT LCD
- Supports 1x Gigabit LAN
- Integrated ALC662 HD Audio CODEC with 6-CH
- **Support CPU smart fan**
- Mini-ITX Form Factor(170mm x 170mm)

| | |
|-----------------|--|
| CPU | INTEL®Atom N270 CPU(45nm,512K Cache, 1.60 GHz, 533 MHz FSB) |
| Chipset | INTEL® 945GSE + ICH7M chipset |
| Memory | Build-in INTEL® GMA 950 Graphics Core(Share Memory Size: 128/224MB) Front Side Bus 533MHz |
| Expansion Slots | 1 * SO-DIMM Sockets for un-buffered Single Channel DDR2 533/400 SDRAM up to 2 GB |
| Storage | 1 * PCI slot 2 * Serial ATA2 3Gb/s connectors 1 * Ultra DMA 100 / 66 IDE connector |
| Audio | Realtek ALC662 6-Channel HD Audio CODEC |
| Ethernet LAN | Realtek RTL8111C PCI-E Gigabit Ethernet LAN |
| LVDS | Onboard 18-bit dual channel LVDS connector |
| USB | Embedded 6 * USB 2.0/1.1 |

| | |
|------------------|---|
| Special Features | Intel Diamond Ville Platform Support ACPI S3 Support CPU Smart FAN Support DC FAN 4 * USB 2.0/1.1 ports 1 * Keyboard connector 1 * RJ-45 port |
| Rear Panel I / O | 3 * Audio I/O ports (Line-in, MIC and line-out) 1 * VGA port 2 * COM port for RS-232 1 * Parallel port 1 * DVI-D port 1 * USB 2.0/1.1 headers for 2 USB 2.0 ports NB / Chassis Fan connectors; 1 * 20-pin ATX Power connector 1 * LVDS header & 1 * GPIO header |
| Internal I / O | 1 * TV-OUT header 1 * HDTV-OUT header 1 * COM4 header for RS-422/485 1 * COM3 header for RS-232 1 * AUDIO header |
| BIOS | Award 8MB SPI/DIP Flash ROM |
| Form Factor | Mini ITX Form Factor(170mmx170mm) |

Product Accessories

- COM cable
- Manual
- CD
- 2x SATA cable
- I/O shield
- 1x IDE cable
- HDTV cable