



89.00 EUR  
incl. 19% VAT, plus [shipping](#)

- INTEL® H61 Express Chipset
- Support 2nd generation Intel Core processor(i3/i5/i7) family
- Multi-monitor support with Windows \* 7
- Support PCI-Express 2.0
- Support USB 3.0
- Support Dual Channel DDR3 1333/1066
- Integrated HD Audio CODEC with 6.0 CH
- Support Gigabit LAN
- 3+1+1 Phase CPU Power Support
- Ready for Windows® 7™
- ITX Form Factor(170mm X 170mm)
  - **INTEL® LGA1155 Socket**
    - Support 2nd generation Intel Core processor(i3/i5/i7) family
    - Support Intel® Pentium® processor, and Intel® Celeron® processor.
    - Support Intel® Turbo Boost Technology 2.0
    - 3+1+1 Phase CPU Power Support
- **CPU**
  - Support Intel® Pentium® processor, and Intel® Celeron® processor.
  - Support Intel® Turbo Boost Technology 2.0
  - 3+1+1 Phase CPU Power Support
- **Chipset**
  - INTEL® H61 Express Chipset
  - Dual Channel DDR3 memory technology
- **Memory**
  - 2 x DDR3 DIMM slots
  - Support DDR3 1333/1066 un-buffered memory
  - Max. capacity of system memory up to: 8GB
- **Expansion Slots**
  - 1x PCI Express 2.0 x16(By 16) slot
- **Storage**
  - 4 x Serial ATA2 3Gb/s connectors
- **Audio**
  - VIA VT1705 Audio CODEC
  - 5.1 CH HD Audio with Content Protection
  - RTL8111E Chip
- **Ethernet LAN**
  - PCI-Ex1 Gigabit LAN 10/100/1000 Mb/s
  - Support PXE
- **USB**
  - 6 x USB 2.0 ports (4 distribute in back panel, 2 distribute in mid-board)
  - 2 x USB 3.0 ports by ASMedia ASM1042 (2 distribute in back panel)

**Embedded INTEL H61 Chipset:**

**INTEL H61 Chipset:**

- 
- **Back Panel I / O**
    - 4 x USB 2.0/1.1 ports
    - 2 x USB 3.0 ports
    - 1 x PS/2 Keyboard / Mouse
    - 1 x VGA Port
    - 1 x DVI-D Port
    - 1 x HDMI Port
    - 1 x RJ-45 Port
    - 3 x Audio jacks (Line In/Line Out/Microphone)
    - 1 x USB 2.0/1.1 header for 2 USB 2.0/1.1 ports
    - CPU / Chassis Fan connectors
  - **Internal I / O**
    - 1 x 4-pin ATX 12V Power connector
    - 1 x 24-pin ATX Power connector
    - 1 x HDMI\_SPDIF header
    - 1 x Front panel audio header
  - **BIOS**
    - 32 MB DIP Flash ROM
  - **Form Factor**
    - ITX form Factor:170x170 mm