



598.00 EUR  
incl. 19% VAT, plus [shipping](#)

- wlan !

- Intel® LGA1151 Socket Core I3,I5,I7 Pentium Processor
- Intel® Coffee Lake-S H310 Chip
- Support Dual Channel DDR4 2133MHz up to 32GB
- 1\* Intel® I219-V GbE LAN + 1\* Intel® i225V 2.5Gb LAN
- Support 1\* SATA III (6Gb/s) & M.2 (M key 2242)
- 1\* M.2 E key Support CNVi
- 4\* RS232 (COM1/2 Support 5V/12V TTL, 4\* USB3.0)
- Support HDMI/VGA /EDP (Option)
- DC 12~24V Input

|                |                                                                                                                                                                                                                                                                             |
|----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model          | <ul style="list-style-type: none"> <li>– HBJC501C8HV-H310</li> <li>– HBJC501C8HVI-H310 (Wifi)</li> </ul>                                                                                                                                                                    |
| CPU/Chipset    | <ul style="list-style-type: none"> <li>– Intel® LGA1151 Socket Core I3,I5,I7 Pentium Processor (TDP 35W)</li> <li>– Intel® Coffee Lake-S H310 Chip</li> </ul>                                                                                                               |
| BIOS           | – AMI 128MB SMT Flash ROM                                                                                                                                                                                                                                                   |
| Memory         | – 2* DDR4 2133MHz up to 32GB                                                                                                                                                                                                                                                |
| Network        | <ul style="list-style-type: none"> <li>– 1* Intel® I219-V GbE</li> <li>– 1* Intel® I225-V 2.5GbE</li> <li>– 1* WIFI2.4/5G + BT4.1 (M.2 E key)</li> </ul>                                                                                                                    |
| Graphics       | <ul style="list-style-type: none"> <li>– 1* HDMI (Max. Resolution : 4096×2160@30Hz)</li> <li>– 1* VGA (Max. Resolution: 1920×1080@60Hz)</li> <li>– 1* eDP (Option, Max. Resolution: 4096×2304@60Hz)</li> <li>– Support Dual Displays or Triple Displays with eDP</li> </ul> |
| Storage        | <ul style="list-style-type: none"> <li>– 1* 2.5" SATA 6Gb/s internal drive bay (only support 2.5" HDD with a hight ≤ 10mm)</li> <li>– 1* M.2 (M-key 2242)</li> </ul>                                                                                                        |
| Expansion slot | <ul style="list-style-type: none"> <li>– 1* PCIe x4 slot</li> <li>– 1* WIFI2.4/5G + BT4.1 (M.2 E key)</li> </ul>                                                                                                                                                            |
| Rear Panel I/O | <ul style="list-style-type: none"> <li>– 4* USB3.0</li> <li>– 1* HDMI</li> <li>– 1* VGA</li> <li>– 1* eDP</li> <li>– 2* RJ45</li> <li>– 4* RS232</li> <li>– 1* Line-out +MIC</li> <li>– 1* DC Jack</li> <li>– 1* Power Button</li> </ul>                                    |

|                    |                                                                                                                               |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Front Panel I/O    | – NA                                                                                                                          |
| Internal Connector | – NA                                                                                                                          |
| Compliance         | – CE, FCC, RoHS, ErP Ready (option)                                                                                           |
| Power Source       | – MB: DC 12~24V input<br>– Adapter: AC_90~240V/ DC_19V / 120W                                                                 |
| Temperature        | – Operating Temperature: -10 ~ 50° C<br>– Storage Temperature: -20 ~ 60° C<br>– Humidity: 10% ~ 90% RH @40°C (non-condensing) |
| Dimensions         | – System: 264 (W) x 199.4 (D) x 58 (H) mm                                                                                     |
| OS Support         | – Windows 10, Linux                                                                                                           |