



CARTFT.COM

398.00 EUR
incl. 19% VAT, plus [shipping](#)

- For Celeron M 1.6Ghz
- FANLESS carpc system
- 12VDC based !
- 4x LAN ports



Support: [Assembling Tutorial \[DE\]](#) | [Assembling Tutorial \[EN\]](#)

Fanless CarPC-barebone for use with Intel P4/Celeron M CPU.
Celeron-M 1.7Ghz is recommended for fanless operation.

| CALU specifications | |
|------------------------------|--|
| Processor (supported) | Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher |
| Memory | Supports DDR 400/333/266 DIMM RAM 0.8" low profile 2x memory slots ! Maximum : 2 GB |
| Video | Intel Extreme Graphics 2 Supports up to 64MB DVMT video memory |
| Audio | Software AC '97 Audio CODEC |

| | |
|------------------------------|---|
| Peripheral Connection | Front : 3 x RJ45 10/100Mb Fast Ethernet 1 x IEEE 1394 Firewire port 1 x USB 2.0 / 1.1 Port 1 x MIC Port 1 x Ear Phone output Jack Power-on button Reset button Power-on and HDD LED Rear : 1 x RS232 COM port 1 x parallel printer port 1 x RJ45 10/100Mb Fast Ethernet 1 x Line-Out output Jack 2 x USB 2.0 / 1.1 Ports 1 x 15 pin VGA 1 x 12v DC Power Jack input |
| Storage | One 2.5 inch Hard Disk and 9.5mm high. (Support Ultra DMA 33/66/100). |
| Weight & Size | System approximately 3kg (fully equipped). System Dimension: 155 x 255 x 55 mm |
| Power req. | 12V, 5A |

Accessory

| | |
|------------------------|---|
| Storage | Supports all Standard Slim CD-ROM/DVD-ROM, CD-RW, DVD-RW Combo Supports all 2.5" standard IDE hard drive, ATA-100/66/33. |
| Scope of supply | 110V/230V EU power supply Barebone CPU Kühlkörper |

Graphics driver for 800x480 resolution : [Here](#)